NSN 5306-01-111-3524

Shear Bolt - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5306-01-111-3524



Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.579 inches and 0.629 inches

Fastener Length:

Between 1.527 inches and 1.557 inches

Head Style:

Spline extended washer

Head Height:

Between 0.247 inches and 0.287 inches

Extended Washer Diameter:

Between 0.575 inches and 0.585 inches

Extended Washer Thickness:

Between 0.035 inches and 0.055 inches

Hole Diameter:

Between 0.050 inches and 0.060 inches

Grip Diameter:

Between 0.3110 inches and 0.3120 inches

Head Minor Diameter:

Between 0.383 inches and 0.389 inches

Thread Diameter:

0.312 inches

Grip Length:

Between 0.928 inches and 0.948 inches

Hole Quantity:

4

Hole Type:

Drilled

Thready Qty Per Inch (tpi):

24

Min. Tensile Strength (psi):

220000 pounds per square inch

Hardness Rating:

46.0 rockwell c and 50.0 rockwell c

Hole Configuration Style:

Spline

Surface Finish:

32.0 microinches grip

Material:

Steel comp h11

NSN 5306-01-111-3524

Shear Bolt - Page 2 of 2



Material Specification: Ams 6487 assn standard single material response Surface Treatment: Cadmium and chromate

Surface Treatment Specification:

Mil-c-8837 type 2 cl 2 military specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

Demilitarization: No Fiig:

A003b0

Mil-std (military Standard):

Mil-c-8837 spec.