
# NSN 5306-01-112-4346

Shear Bolt - Page 1 of 2





#### **Thread Class:**

3a

**Thread Direction:** 

Right-hand

## Thread Length:

Between 0.298 inches and 0.348 inches

## Fastener Length:

Between 2.433 inches and 2.463 inches

## Head Style:

Dished hexagon

## Head Height:

Between 0.110 inches and 0.125 inches

## Width Between Flats:

Between 0.367 inches and 0.376 inches

## Grip Diameter:

Between 0.1890 inches and 0.1895 inches

Thread Diameter:

0.190 inches

# Grip Length:

Between 2.115 inches and 2.135 inches

# Thready Qty Per Inch (tpi):

32

## Min. Tensile Strength (psi):

160000 pounds per square inch

#### Surface Finish:

32.0 microinches threads

#### Material:

Iron alloy 660

# Material Specification:

Ams 5731 assn standard single material response or ams 5737 assn standard single material response

## Surface Treatment:

Passivate

# **Thread Series Designator:**

Unjf

# **Specification Data:**

80205-nas6303 professional/industrial association standard

# Shelf Life:

N/a

# Unit Of Measure:

--

### Demilitarization:

No

# NSN 5306-01-112-4346

Shear Bolt - Page 2 of 2

Fiig: A003b0

