

View Online at <https://aerobasegroup.com/nsn/5306-01-112-7899>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.684 inches and 0.704 inches

Fastener Length:

1.881 inches

Head Style:

Double hexagon

Head Height:

0.257 inches

Width Between Flats:

Between 0.678 inches and 0.689 inches

Grip Diameter:

Between 0.4360 inches and 0.4370 inches

Thread Diameter:

0.438 inches

Grip Length:

Between 1.177 inches and 1.197 inches

Thready Qty Per Inch (tpi):

20

Min. Tensile Strength (psi):

180000 pounds per square inch

Hardness Rating:

39.0 rockwell c and 43.0 rockwell c

Material:

Steel comp e4340 or steel comp h11

Material Specification:

Mil-s-5000 military specification 1st material response or ams 6485 assn standard 2nd material response

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Nas672 assn standard 1st treatment response and qq-p-416 type 2 federal specification 2nd treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0

Mil-std (military Standard):

Mil-s-5000 spec.