## NSN 5306-01-112-7900

Shear Bolt - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5306-01-112-7900

## **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

## Thread Length:

Between 0.437 inches and 0.457 inches

#### Fastener Length:

0.884 inches

#### Head Style:

Double hexagon

#### **Head Height:**

0.187 inches

#### Width Between Flats:

Between 0.492 inches and 0.502 inches

#### Grip Diameter:

Between 0.3110 inches and 0.3120 inches

#### **Thread Diameter:**

0.312 inches

## Grip Length:

Between 0.427 inches and 0.447 inches

## Thready Qty Per Inch (tpi):

24

## Min. Tensile Strength (psi):

180000 pounds per square inch

## Hardness Rating:

39.0 rockwell c and 43.0 rockwell c

#### Material:

Steel comp e4340 or steel comp h11

## Material Specification:

Mil-s-5000 military specification 1st material response or ams 6485 assn standard 2nd material response

#### Surface Treatment:

Cadmium and chromate

## Surface Treatment Specification:

Nas672 assn standard 1st treatment response and qq-p-416 type 2 federal specification 2nd treatment response

## Thread Series Designator:

Unjf

## Shelf Life:

N/a

## Unit Of Measure:

---

## Demilitarization:

No



# NSN 5306-01-112-7900

Shear Bolt - Page 2 of 2

**Fiig:** A003b0

Mil-std (military Standard):

Mil-s-5000 spec.

