

View Online at <https://aerobasegroup.com/nsn/5306-01-112-8682>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.657 inches and 0.875 inches

**Fastener Length:**

Between 0.813 inches and 0.875 inches

**Head Style:**

Hexagon

**Head Height:**

Between 0.226 inches and 0.243 inches

**Width Between Flats:**

Between 0.551 inches and 0.562 inches

**Locking Feature:**

Patch threads or strip threads

**Thread Diameter:**

0.375 inches

**Features Provided:**

Finished head

**Thready Qty Per Inch (tpi):**

16

**Min. Tensile Strength (psi):**

150000 pounds per square inch

**Hardness Rating:**

32.0 rockwell c fastener and 38.0 rockwell c fastener

**Special Features:**

Locking feature is plastic polyamide

**Material:**

Steel

**Material Specification:**

Sae j429, grade8 assn standard single material response fastener or astm a354, grade bd assn standard single material response fastener

**Surface Treatment:**

Zinc fastener and chromate fastener

**Surface Treatment Specification:**

Astm b633 type 2 sc 3 assn standard single treatment response fastener

**Thread Series Designator:**

Unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0