

View Online at <https://aerobasegroup.com/nsn/5306-01-113-9761>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.397 inches and 0.447 inches

**Fastener Length:**

Between 0.845 inches and 0.875 inches

**Head Style:**

Spline extended washer

**Head Height:**

Between 0.158 inches and 0.198 inches

**Width Between Flats:**

Between 0.253 inches and 0.259 inches

**Extended Washer Diameter:**

Between 0.349 inches and 0.359 inches

**Extended Washer Thickness:**

Between 0.017 inches and 0.037 inches

**Grip Diameter:**

Between 0.1885 inches and 0.1895 inches

**Thread Diameter:**

0.190 inches

**Grip Length:**

Between 0.428 inches and 0.448 inches

**Thready Qty Per Inch (tpi):**

32

**Min. Tensile Strength (psi):**

220000 pounds per square inch

**Hardness Rating:**

46.0 rockwell c and 50.0 rockwell c

**Surface Finish:**

32.0 microinches grip

**Material:**

Steel comp h11

**Material Specification:**

Ams 6487 assn standard single material response

**Surface Treatment:**

Cadmium and chromate

**Surface Treatment Specification:**

Mil-c-8837 type 2 cl 2 military specification single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0

**Mil-std (military Standard):**

Mil-c-8837 spec.