

View Online at <https://aerobasegroup.com/nsn/5306-01-115-2515>

**Thread Direction:**

Right-hand

**Thread Length:**

Between 14.0 millimeters and 15.0 millimeters

**Fastener Length:**

Between 36.20 millimeters and 36.80 millimeters

**Head Style:**

Undercut hexagon

**Head Height:**

Between 4.7 millimeters and 5.0 millimeters

**Width Between Flats:**

Between 16.73 millimeters and 17.00 millimeters

**Grip Diameter:**

Between 9.9620 millimeters and 9.9870 millimeters

**Thread Diameter:**

10.0 millimeters

**Grip Length:**

Between 21.80 millimeters and 22.20 millimeters

**Min. Tensile Strength (psi):**

1100 megapascals

**Hardness Rating:**

36.0 rockwell c and 40.0 rockwell c

**Thread Pitch In Millimeters:**

1.25

**Surface Finish:**

0.8 micrometers threads

**Material:**

Steel comp e4340 or steel comp 8740

**Material Specification:**

Mil-s-5000 military specification 1st material response or mil-s-6049 military specification 2nd material response

**Surface Treatment:**

Cadmium and chromate

**Surface Treatment Specification:**

Qq-p-416 type 2 cl 2 federal specification single treatment response

**Thread Series Designator:**

Mj

**Specification Data:**

80205-na0036 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0

**Mil-std (military Standard):**

Mil-s-5000 spec.