

View Online at <https://aerobasegroup.com/nsn/5306-01-116-1195>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.589 inches and 0.639 inches

Fastener Length:

Between 3.349 inches and 3.379 inches

Head Style:

Spline extended washer

Head Height:

Between 0.263 inches and 0.303 inches

Extended Washer Diameter:

Between 0.691 inches and 0.701 inches

Extended Washer Thickness:

Between 0.044 inches and 0.064 inches

Grip Diameter:

Between 0.3740 inches and 0.3745 inches

Shank Unthreaded Hole Diameter:

0.106 inches first hole and 0.111 inches first hole

Head Minor Diameter:

Between 0.448 inches and 0.455 inches

Thread Diameter:

0.375 inches

Grip Length:

Between 2.740 inches and 2.760 inches

Thready Qty Per Inch (tpi):

24

Min. Tensile Strength (psi):

220000 pounds per square inch

Distance From Head Largest Bearing Surface To Shank Hole Center:

3.126 inches first hole and 3.166 inches first hole

Material:

Steel comp xm-13

Material Specification:

Ams 5629 assn standard single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0