NSN 5306-01-116-6608

Machine Bolt - Page 1 of 2

Thread Class:



View Online at https://aerobasegroup.com/nsn/5306-01-116-6608

3a
Thread Direction:
Right-hand
Thread Length:
Between 0.680 inches and 0.740 inches
Fastener Length:
Between 1.740 inches and 1.760 inches
Head Style:
Double hexagon w/hole
Head Height:
Between 0.250 inches and 0.270 inches
Width Between Flats:
0.250 inches
Extended Washer Diameter:
Between 0.365 inches and 0.385 inches
Extended Washer Thickness:
0.040 inches
Hole Diameter:
Between 0.037 inches and 0.057 inches
Thread Diameter:
0.190 inches
Grip Length:
Between 1.020 inches and 1.060 inches
Hole Quantity:
4
Hole Type:
Drilled
Features Provided:
Finished head
Thready Qty Per Inch (tpi):
32
Min. Tensile Strength (psi):
130000 pounds per square inch
Hardness Rating:
24.0 rockwell c and 35.0 rockwell c
Minimum Yield Strength:
85000 pounds per square inch
Hole Configuration Style:
Double hexagon longitudinal hole
Surface Finish:
32.0 microinches threads

NSN 5306-01-116-6608 Machine Bolt - Page 2 of 2



Fiig: A003b0