## NSN 5306-01-116-6614

Assembled Washer Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-116-6614 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.369 inches and 0.500 inches **Fastener Length:** Between 0.469 inches and 0.500 inches **Head Style:** Hexagon **Head Height:** Between 0.172 inches and 0.190 inches Width Between Flats: Between 0.428 inches and 0.438 inches Washer Quantity: **Thread Diameter:** 0.250 inches Thready Qty Per Inch (tpi): 20 **Hardness Rating:** 40.0 rockwell c primary washer and 50.0 rockwell c primary washer **Primary Washer Outside Diameter:** Between 0.466 inches and 0.478 inches **Primary Washer Style:** Flat internal teeth **Primary Washer Material Thickness:** 0.025 inches **Special Features:** With header point Material: Steel comp 1050 primary washer and steel comp 1566 primary washer **Material Specification:** Sae assn standard single material response fastener **Surface Treatment:** Cadmium primary washer or zinc primary washer **Thread Series Designator:** Unc Shelf Life:

N/a **Unit Of Measure:** --

## NSN 5306-01-116-6614

Assembled Washer Bolt - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0