## NSN 5306-01-116-9167

Machine Bolt - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5306-01-116-9167



#### **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

## Thread Length:

Between 0.955 inches and 1.032 inches

#### Fastener Length:

Between 1.015 inches and 1.062 inches

#### Head Style:

Hexagon

Head Height:

Between 0.365 inches and 0.385 inches

#### Width Between Flats:

Between 0.740 inches and 0.752 inches

#### Hole Diameter:

Between 0.070 inches and 0.080 inches

#### **Thread Diameter:**

0.500 inches

## Grip Length:

Between 0.030 inches and 0.060 inches

#### Hole Quantity:

3

#### Hole Type:

Drilled

#### Features Provided:

Finished head

#### Thready Qty Per Inch (tpi):

20

#### Hardness Rating:

36.0 rockwell c and 40.0 rockwell c

#### Minimum Yield Strength:

160000 pounds per square inch

#### Hole Configuration Style:

Hexagon corners

#### Material:

Steel comp 4140 or steel comp 8740 or steel comp 8630 or steel comp 8735 or steel comp 4130 or steel comp 4037

#### Surface Treatment:

Cadmium and chromate

## Surface Treatment Specification:

Qq-p-416, type 2 cl 2 federal specification single treatment response

#### **Thread Series Designator:**

Unjf

# NSN 5306-01-116-9167

Machine Bolt - Page 2 of 2



**Specification Data:** 

80205-nas568 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

---

## Demilitarization:

No

Fiig:

A003b0