

View Online at <https://aerobasegroup.com/nsn/5306-01-117-2397>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 1.066 inches and 1.106 inches

**Fastener Length:**

Between 5.326 inches and 5.346 inches

**Head Style:**

Spline drive shear head

**Head Height:**

Between 0.351 inches and 0.381 inches

**Width Between Flats:**

Between 0.774 inches and 0.782 inches

**Grip Diameter:**

Between 0.6235 inches and 0.6240 inches

**Shank Unthreaded Hole Diameter:**

0.141 inches first hole and 0.146 inches first hole

**Thread Diameter:**

0.625 inches

**Grip Length:**

Between 4.240 inches and 4.260 inches

**Thready Qty Per Inch (tpi):**

18

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

5.076 inches first hole and 5.106 inches first hole

**Material:**

Stainless steel

**Material Specification:**

23-112 fscm 76301 mfr ref single material response

**Surface Treatment:**

Passivate

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0