## NSN 5306-01-118-4876

Machine Bolt - Page 1 of 2

**Thread Class:** 

N/a

View Online at https://aerobasegroup.com/nsn/5306-01-118-4876



3a **Thread Direction: Right-hand Thread Length:** Between 0.620 inches and 0.700 inches Fastener Length: Between 0.802 inches and 0.822 inches **Head Style:** Double hexagon w/hole **Head Height:** Between 0.248 inches and 0.268 inches Width Between Flats: 0.250 inches **Extended Washer Diameter:** Between 0.365 inches and 0.385 inches **Extended Washer Thickness:** 0.040 inches **Thread Diameter:** 0.190 inches Grip Length: Between 0.122 inches and 0.182 inches **Features Provided:** Finished head Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 140000 pounds per square inch Hardness Rating: 32.0 rockwell c and 38.0 rockwell c Minimum Yield Strength: 120000 pounds per square inch Surface Finish: 32.0 microinches threads Material: Steel comp 630 **Material Specification:** Ams5643 assn standard single material response **Thread Series Designator:** Unjf Shelf Life:

## NSN 5306-01-118-4876

Machine Bolt - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A003b0

