## NSN 5306-01-118-4877



Machine Bolt - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5306-01-118-4877 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 1.375 inches **Fastener Length:** Between 1.420 inches and 1.560 inches **Head Style:** Hexagon **Head Height:** Between 0.455 inches and 0.483 inches Width Between Flats: Between 1.212 inches and 1.250 inches **Thread Diameter:** 0.750 inches **Features Provided:** Finished head Thready Qty Per Inch (tpi): 10 Min. Tensile Strength (psi): 120000 pounds per square inch **Hardness Rating:** 23.0 rockwell c and 34.0 rockwell c Minimum Yield Strength: 90000 pounds per square inch **Product Name:** Navy special project Material: Steel comp 1013 or steel comp 1015 or steel comp 1016 or steel comp 1017 or steel comp 1018 or steel comp 1019 or steel comp 1020 or steel comp 1021 or steel comp 1022 or steel comp 1023 or steel comp 1025 or steel comp 1026 or steel comp 1029 or steel comp 1030 or steel comp 1033 or steel comp 1034 or steel comp 1035 or steel comp 1037 or steel comp 1038 or steel comp 1039 or steel comp 1040 or steel comp 1524 or steel comp 1527 or steel comp 1536 or steel comp 1541 **Material Specification:** 66 federal standard all material responses **Surface Treatment:** Zinc **Surface Treatment Specification:** Astm b633 type 2 cl fe/zn 13 assn standard single treatment response

Unit Of Measure:

Unc

N/a

Shelf Life:

**Thread Series Designator:** 

## NSN 5306-01-118-4877

Machine Bolt - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0