
## NSN 5306-01-118-4887

Machine Bolt - Page 1 of 2





### Thread Class:

2a

**Thread Direction:** 

**Right-hand** 

#### Thread Length:

Between 0.865 inches and 1.000 inches

#### Fastener Length:

Between 0.969 inches and 1.000 inches

#### Head Style:

Hexagon

Head Height:

Between 0.226 inches and 0.243 inches

#### Width Between Flats:

Between 0.551 inches and 0.562 inches

#### Locking Feature:

#### Patch threads or strip threads

Thread Diameter:

0.375 inches

#### **Features Provided:**

Finished head

#### Thready Qty Per Inch (tpi):

24

#### Min. Tensile Strength (psi):

150000 pounds per square inch

#### Hardness Rating:

32.0 rockwell c fastener and 38.0 rockwell c fastener

#### **Special Features:**

Locking feature plastic polyamide

#### Material:

Steel

#### **Material Specification:**

Astm a354, grade bd assn standard 1st material response

#### Surface Treatment:

Zinc fastener and chromate fastener

#### Surface Treatment Specification:

Astm b633 type 2 sc 3 assn standard single treatment response fastener

#### **Thread Series Designator:**

Unf

#### Shelf Life:

N/a

#### Unit Of Measure:

---

# **NSN 5306-01-118-4887** Machine Bolt - Page 2 of 2

Demilitarization:

No

Fiig:

A003b0

