NSN 5306-01-119-4272

Shear Bolt - Page 1 of 2

Thread Class:

Right-hand

Thread Direction:

За



View Online at https://aerobasegroup.com/nsn/5306-01-119-4272

Thread Length: Between 0.753 inches and 0.803 inches **Fastener Length:** Between 1.388 inches and 1.418 inches **Head Style:** Spline extended washer **Head Height:** Between 0.325 inches and 0.355 inches **Extended Washer Diameter:** Between 0.807 inches and 0.817 inches **Extended Washer Thickness:** Between 0.048 inches and 0.058 inches **Grip Diameter:** Between 0.4360 inches and 0.4370 inches **Head Minor Diameter:** Between 0.514 inches and 0.521 inches **Thread Diameter:** 0.438 inches **Grip Length:** Between 0.615 inches and 0.635 inches Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 220000 pounds per square inch **Hardness Rating:** 46.0 rockwell c and 50.0 rockwell c **Surface Finish:** 32.0 microinches grip Material: Steel comp h11 **Material Specification:** Ams6487 assn standard single material response **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Mil-c-8837, type 2, class 2 military specification single treatment response **Thread Series Designator:** Unjf

NSN 5306-01-119-4272

Shear Bolt - Page 2 of 2



N/a	
Unit Of Measure:	
Demilitarization:	
No	
Fiig:	

Mil-std (military Standard):

Mil-c-8837 spec.

Shelf Life: