NSN 5306-01-119-8884

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-119-8884

Thread Class
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.716 inches and 0.766 inches
Fastener Length:
Between 4.538 inches and 4.568 inches
Head Style:
Double hexagon w/hole
Head Height:
Between 0.494 inches and 0.514 inches
Width Between Flats:
Between 0.553 inches and 0.564 inches
Extended Washer Diameter:
Between 0.818 inches and 0.828 inches
Extended Washer Thickness:
Between 0.113 inches and 0.133 inches
Grip Diameter:
Between 0.4985 inches and 0.4995 inches
Thread Diameter:
0.500 inches
Grip Length:
Between 3.802 inches and 3.822 inches
Thready Qty Per Inch (tpi):
20
Min. Tensile Strength (psi):
180000 pounds per square inch
Surface Finish:
32.0 microinches threads
Material:
Steel comp 4340 or steel comp e4340 or steel comp 8740
Surface Treatment:
Cadmium
Surface Treatment Specification:
Nas 672 assn standard single treatment response
Thread Series Designator:
Unif
Shelf Life:
N/a
Unit Of Measure:
om of mousure.

--

NSN 5306-01-119-8884

Shear Bolt - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0