NSN 5306-01-120-5115

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-120-5115 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.903 inches and 0.953 inches **Fastener Length:** Between 2.663 inches and 2.693 inches **Head Style:** Spline extended washer **Head Height:** Between 0.440 inches and 0.460 inches **Extended Washer Diameter:** Between 0.818 inches and 0.828 inches **Extended Washer Thickness:** Between 0.092 inches and 0.112 inches **Grip Diameter:** Between 0.4985 inches and 0.4995 inches **Head Minor Diameter:** Between 0.644 inches and 0.651 inches **Thread Diameter:** 0.500 inches **Grip Length:** Between 1.740 inches and 1.760 inches Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 220000 pounds per square inch **Hardness Rating:** 46.0 rockwell c and 50.0 rockwell c **Surface Finish:** 32.0 microinches grip

Special Features:

Color blue per federal standard 595 no. 15102

Material:

Steel comp h11

Material Specification:

Ams6487 assn standard single material response

Surface Treatment:

Cadmium grip and chromate grip

Surface Treatment Specification:

Tt-e-489 federal specification single treatment response top of head

NSN 5306-01-120-5115

Shear Bolt - Page 2 of 2



Thread Series Designator:
Unjf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A003b0
Mil-std (military Standard):

Mil-c-8837 spec.