## NSN 5306-01-120-9410

Shoulder Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-120-9410 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.505 inches **Fastener Length:** 1.960 inches **Head Style:** Hexagon **Head Height:** 0.130 inches Width Between Flats: 0.875 inches **Shoulder Diameter:** 0.623 inches first shoulder and 0.624 inches first shoulder **Shoulder Length:** 1.445 inches first shoulder and 1.455 inches first shoulder **Thread Diameter:** 0.562 inches Thready Qty Per Inch (tpi): 18 Min. Tensile Strength (psi): 280000 pounds per square inch **Criticality Code Justification:** Aatn **Shoulder Shape:** Round first shoulder **Special Features:** Hole drilled 0.280 in. Diameter by 1.990 in. Lg; two keyways 0.125 in. Min to 0.130 in. Maximum wide by 0.400 in. Min to 0.410 in. Maximum lg Material: Steel **Material Specification:** Mil-s-8844 class 3, cond e-2 military specification single material response **Thread Series Designator:** Unjf Shelf Life: N/a **Unit Of Measure:** 

No

Demilitarization:

## NSN 5306-01-120-9410

Shoulder Bolt - Page 2 of 2



Fiig:

A003b0

Mil-std (military Standard):

Mil-s-8844 spec.