## NSN 5306-01-120-9910

Shear Bolt - Page 1 of 2

**Thread Class:** 

3a

Unjf

View Online at https://aerobasegroup.com/nsn/5306-01-120-9910



## **Thread Direction: Right-hand Thread Length:** Between 0.709 inches and 0.759 inches Fastener Length: Between 1.844 inches and 1.874 inches **Head Style:** Spline extended washer **Head Height:** Between 0.263 inches and 0.303 inches Width Between Flats: Between 0.448 inches and 0.455 inches **Extended Washer Diameter:** Between 0.691 inches and 0.701 inches **Extended Washer Thickness:** Between 0.044 inches and 0.064 inches **Grip Diameter:** Between 0.3735 inches and 0.3745 inches **Thread Diameter:** 0.375 inches Grip Length: Between 1.115 inches and 1.135 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 260000 pounds per square inch Hardness Rating: 51.0 rockwell c and 54.0 rockwell c Surface Finish: 32.0 microinches grip Material: Steel comp h11 **Material Specification:** Ams 6487 assn standard single material response **Surface Treatment:** Cadmium **Surface Treatment Specification:** Mil-c-8837, type 2 cl 2 military specification single treatment response **Thread Series Designator:**

## NSN 5306-01-120-9910

Shear Bolt - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A003b0

## Mil-std (military Standard):

Mil-c-8837 spec.

