

View Online at <https://aerobasegroup.com/nsn/5306-01-121-0339>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.370 inches

Fastener Length:

3.058 inches

Head Style:

Dished hexagon

Head Height:

Between 0.125 inches and 0.140 inches

Width Between Flats:

Between 0.429 inches and 0.439 inches

Grip Diameter:

Between 0.2485 inches and 0.2495 inches

Single Shear Strength:

95000 pounds per square inch

Thread Diameter:

0.250 inches

Grip Length:

2.688 inches

Features Provided:

Finished head

Thready Qty Per Inch (tpi):

28

Min. Tensile Strength (psi):

160000 pounds per square inch

Hardness Rating:

36.0 rockwell c and 40.0 rockwell c

Surface Finish:

32.0 microinches grip

Material:

Steel comp e4340 or steel comp 8740

Material Specification:

Mil-s-5000 military specification 1st material response or mil-s-6049 military specification 2nd material response or ams6322 assn standard 3rd material response

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416, ty2, cl2 federal specification single treatment response

Thread Series Designator:

Unf

Specification Data:

80205-nas6204 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5000 spec.