## NSN 5306-01-121-2708

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-121-2708

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.320 inches and 0.370 inches
Fastener Length:
Between 1.080 inches and 1.110 inches
Head Style:
Dished hexagon
Head Height:
Between 0.110 inches and 0.125 inches
Width Between Flats:
Between 0.367 inches and 0.376 inches
Grip Diameter:
Between 0.2016 inches and 0.2026 inches
Thread Diameter:
0.190 inches
Grip Length:
Between 0.740 inches and 0.760 inches
Thready Qty Per Inch (tpi):
32
Min. Tensile Strength (psi):
160000 pounds per square inch
Hardness Rating:
36.0 rockwell c and 40.0 rockwell c
Surface Finish:
32.0 microinches threads
Material:
Steel comp e4340 or steel comp 4340 or steel comp 8740
Surface Treatment:
Cadmium and chromate
Surface Treatment Specification:
Qq-p-416, type 2, class 2 federal specification single treatment response
Thread Series Designator:
Unjf
Specification Data:
80205-nas6603 professional/industrial association standard
Shelf Life:
N/a
Unit Of Measure:

## NSN 5306-01-121-2708

Shear Bolt - Page 2 of 2



em			

No

Fiig:

A003b0