NSN 5306-01-122-0461

Machine Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-122-0461

View Online at https://aerobasegroup.com/nsn/5306-01-122-0461
Thread Class:
2a
Thread Direction:
Right-hand
Thread Length:
Between 0.505 inches and 0.625 inches
Fastener Length:
Between 0.594 inches and 0.625 inches
Head Style:
Hexagon
Head Height:
Between 0.150 inches and 0.163 inches
Width Between Flats:
Between 0.428 inches and 0.438 inches
Locking Feature:
Patch threads or strip threads
Thread Diameter:
0.250 inches
Features Provided:
Finished head
Thready Qty Per Inch (tpi):
rineday aty i or mon (tpi).
28
28
28 Min. Tensile Strength (psi):
28 Min. Tensile Strength (psi): 150000 pounds per square inch
Min. Tensile Strength (psi): 150000 pounds per square inch Hardness Rating:
Min. Tensile Strength (psi): 150000 pounds per square inch Hardness Rating: 32.0 rockwell c fastener and 38.0 rockwell c fastener
Min. Tensile Strength (psi): 150000 pounds per square inch Hardness Rating: 32.0 rockwell c fastener and 38.0 rockwell c fastener Minimum Yield Strength:
Min. Tensile Strength (psi): 150000 pounds per square inch Hardness Rating: 32.0 rockwell c fastener and 38.0 rockwell c fastener Minimum Yield Strength: 60000 pounds per square inch
Min. Tensile Strength (psi): 150000 pounds per square inch Hardness Rating: 32.0 rockwell c fastener and 38.0 rockwell c fastener Minimum Yield Strength: 60000 pounds per square inch Material:
Min. Tensile Strength (psi): 150000 pounds per square inch Hardness Rating: 32.0 rockwell c fastener and 38.0 rockwell c fastener Minimum Yield Strength: 60000 pounds per square inch Material: Steel fastener
Min. Tensile Strength (psi): 150000 pounds per square inch Hardness Rating: 32.0 rockwell c fastener and 38.0 rockwell c fastener Minimum Yield Strength: 60000 pounds per square inch Material: Steel fastener Material Specification:
Min. Tensile Strength (psi): 150000 pounds per square inch Hardness Rating: 32.0 rockwell c fastener and 38.0 rockwell c fastener Minimum Yield Strength: 60000 pounds per square inch Material: Steel fastener Material Specification: Sae j429 grade 8 assn standard single material response fastener
Min. Tensile Strength (psi): 150000 pounds per square inch Hardness Rating: 32.0 rockwell c fastener and 38.0 rockwell c fastener Minimum Yield Strength: 60000 pounds per square inch Material: Steel fastener Material Specification: Sae j429 grade 8 assn standard single material response fastener Surface Treatment:
Min. Tensile Strength (psi): 150000 pounds per square inch Hardness Rating: 32.0 rockwell c fastener and 38.0 rockwell c fastener Minimum Yield Strength: 60000 pounds per square inch Material: Steel fastener Material Specification: Sae j429 grade 8 assn standard single material response fastener Surface Treatment: Zinc fastener and chromate fastener
Min. Tensile Strength (psi): 150000 pounds per square inch Hardness Rating: 32.0 rockwell c fastener and 38.0 rockwell c fastener Minimum Yield Strength: 60000 pounds per square inch Material: Steel fastener Material Specification: Sae j429 grade 8 assn standard single material response fastener Surface Treatment: Zinc fastener and chromate fastener Surface Treatment Specification:
Min. Tensile Strength (psi): 150000 pounds per square inch Hardness Rating: 32.0 rockwell c fastener and 38.0 rockwell c fastener Minimum Yield Strength: 60000 pounds per square inch Material: Steel fastener Material Specification: Sae j429 grade 8 assn standard single material response fastener Surface Treatment: Zinc fastener and chromate fastener Surface Treatment Specification: Astm b633 type 2 sc 3 assn standard single treatment response fastener
Min. Tensile Strength (psi): 150000 pounds per square inch Hardness Rating: 32.0 rockwell c fastener and 38.0 rockwell c fastener Minimum Yield Strength: 60000 pounds per square inch Material: Steel fastener Material Specification: Sae j429 grade 8 assn standard single material response fastener Surface Treatment: Zinc fastener and chromate fastener Surface Treatment Specification: Astm b633 type 2 sc 3 assn standard single treatment response fastener Thread Series Designator:
Min. Tensile Strength (psi): 150000 pounds per square inch Hardness Rating: 32.0 rockwell c fastener and 38.0 rockwell c fastener Minimum Yield Strength: 60000 pounds per square inch Material: Steel fastener Material Specification: Sae j429 grade 8 assn standard single material response fastener Surface Treatment: Zinc fastener and chromate fastener Surface Treatment Specification: Astm b633 type 2 sc 3 assn standard single treatment response fastener Thread Series Designator: Unf

N/a

NSN 5306-01-122-0461 Machine Bolt - Page 2 of 2



	• •				
In	18	<i>(</i>)+	МЛО	201	ure:

Demilitarization:

No

Fiig:

A003b0