## NSN 5306-01-122-2057

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-122-2057 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.396 inches and 0.463 inches **Fastener Length:** Between 5.406 inches and 5.453 inches **Head Style:** Hexagon **Head Height:** Between 0.234 inches and 0.266 inches Width Between Flats: Between 0.740 inches and 0.752 inches **Grip Diameter:** Between 0.4982 inches and 0.4991 inches **Thread Diameter:** 0.500 inches **Grip Length:** Between 4.990 inches and 5.010 inches Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 36.0 rockwell c and 40.0 rockwell c Material: Steel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 8735 or steel comp 6150 **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416, type 2, class 2 federal specification single treatment response **Thread Series Designator:** Unjf **Specification Data:** 80205-nas464 professional/industrial association standard Shelf Life: N/a **Unit Of Measure:** 

No

**Demilitarization:** 

## NSN 5306-01-122-2057

Shear Bolt - Page 2 of 2



Fiig:

A003b0