NSN 5306-01-122-3196



Shear Bolt - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5306-01-122-3196 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.716 inches and 0.766 inches **Fastener Length:** Between 3.914 inches and 3.944 inches **Head Style:** Double hexagon w/hole **Head Height:** Between 0.494 inches and 0.514 inches Width Between Flats: Between 0.553 inches and 0.564 inches

Extended Washer Diameter:

Between 0.818 inches and 0.828 inches

Extended Washer Thickness:

Between 0.113 inches and 0.133 inches

Grip Diameter:

Between 0.4985 inches and 0.4995 inches

Thread Diameter:

0.500 inches

Grip Length:

Between 3.178 inches and 3.198 inches

Thready Qty Per Inch (tpi):

20

Min. Tensile Strength (psi):

180000 pounds per square inch

Surface Finish:

32.0 microinches threads

Material:

Steel comp 4340 or steel comp e4340 or steel comp 8740

Surface Treatment:

Cadmium

Surface Treatment Specification:

Nas 672 assn standard single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

NSN 5306-01-122-3196

Shear Bolt - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0