
## NSN 5306-01-122-4697

Shear Bolt - Page 1 of 2





## **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

## Thread Length:

Between 0.320 inches and 0.370 inches

#### Fastener Length:

Between 2.455 inches and 2.485 inches

#### **Head Style:**

Dished hexagon

#### **Head Height:**

Between 0.110 inches and 0.125 inches

#### Width Between Flats:

Between 0.367 inches and 0.376 inches

#### Grip Diameter:

Between 0.1890 inches and 0.1895 inches

## **Thread Diameter:**

0.190 inches

## Grip Length:

Between 2.115 inches and 2.135 inches

## Thready Qty Per Inch (tpi):

32

## Min. Tensile Strength (psi):

160000 pounds per square inch

## Surface Finish:

32.0 microinches threads

## Material:

Iron alloy 660

## **Material Specification:**

Ams 5731 assn standard single material response or ams 5737 assn standard single material response

#### Surface Treatment:

Passivate

## Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

## **Thread Series Designator:**

Unjf

#### **Specification Data:**

80205-nas6703 professional/industrial association standard

#### Shelf Life:

N/a

#### Unit Of Measure:

---

# NSN 5306-01-122-4697

Shear Bolt - Page 2 of 2

Demilitarization:

No

Fiig:

A003b0

