NSN 5306-01-122-4698

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-122-4698 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.716 inches and 0.766 inches **Fastener Length:** Between 3.538 inches and 3.568 inches **Head Style:** Double hexagon w/hole **Head Height:** Between 0.494 inches and 0.514 inches Width Between Flats: Between 0.553 inches and 0.564 inches **Extended Washer Diameter:** Between 0.818 inches and 0.828 inches **Extended Washer Thickness:** Between 0.113 inches and 0.133 inches **Grip Diameter:** Between 0.4985 inches and 0.4995 inches **Thread Diameter:** 0.500 inches **Grip Length:** Between 2.802 inches and 2.822 inches Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 180000 pounds per square inch Surface Finish: 32.0 microinches threads Material: Steel comp 4340 or steel comp e4340 or steel comp 8740 **Surface Treatment:** Cadmium **Surface Treatment Specification:** Nas 672 assn standard single treatment response **Thread Series Designator:** Unjf Shelf Life:

Unit Of Measure:

N/a

NSN 5306-01-122-4698

Shear Bolt - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0