## NSN 5306-01-123-0898

Shear Bolt - Page 1 of 2

**Thread Class:** 

Right-hand **Thread Length:**0.589 inches

**Thread Direction:** 

Fastener Length:

**Head Style:** 

Between 1.714 inches and 1.744 inches

2a



View Online at https://aerobasegroup.com/nsn/5306-01-123-0898

Spline extended washer
Head Height:
Between 0.247 inches and 0.287 inches
Extended Washer Diameter:
Between 0.575 inches and 0.585 inches
Extended Washer Thickness:
Between 0.020 inches and 0.050 inches
Grip Diameter:
Between 0.3110 inches and 0.3120 inches
Head Minor Diameter:
Between 0.383 inches and 0.389 inches
Thread Diameter:
0.312 inches
Grip Length:
Between 1.115 inches and 1.235 inches
Features Provided:
Finished head
Thready Qty Per Inch (tpi):
24
Min. Tensile Strength (psi):
220000 pounds per square inch
Hardness Rating:
46.0 rockwell c and 50.0 rockwell c
Minimum Yield Strength:
215000 pounds per square inch
Surface Finish:
32.0 microinches grip
Material:
Steel comp h11
Material Specification:
Ams 6487 assn standard single material response
Surface Treatment:
Cadmium

## NSN 5306-01-123-0898

Shear Bolt - Page 2 of 2



Surface Treatment Speci
-------------------------

Mil-c-8837, ty2, cl2 military specification single treatment response

**Thread Series Designator:** 

Unf

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-c-8837 spec.