

View Online at <https://aerobasegroup.com/nsn/5306-01-123-6359>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.429 inches and 0.465 inches

**Fastener Length:**

Between 1.945 inches and 1.965 inches

**Head Style:**

Dished hexagon

**Head Height:**

Between 0.126 inches and 0.141 inches

**Width Between Flats:**

Between 0.430 inches and 0.439 inches

**Grip Diameter:**

Between 0.2490 inches and 0.2495 inches

**Shank Unthreaded Hole Diameter:**

0.076 inches all holes and 0.086 inches all holes

**Thread Diameter:**

0.250 inches

**Grip Length:**

Between 1.500 inches and 1.516 inches

**Thready Qty Per Inch (tpi):**

28

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

0.860 inches all holes and 0.890 inches all holes

**Surface Finish:**

63.0 microinches grip

**Special Features:**

With retaining element on shank and two holes spaced ninety degrees apart

**Material:**

Steel comp xm-13

**Material Specification:**

Ams5629 assn standard single material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0