

View Online at <https://aerobasegroup.com/nsn/5306-01-123-9779>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.400 inches and 0.450 inches

Fastener Length:

Between 1.098 inches and 1.128 inches

Head Style:

Dished hexagon

Head Height:

Between 0.125 inches and 0.140 inches

Width Between Flats:

Between 0.430 inches and 0.439 inches

Locking Feature:

Pellet threads or strip threads or patch threads

Grip Diameter:

Between 0.2485 inches and 0.2495 inches

Thread Diameter:

0.250 inches

Grip Length:

Between 0.678 inches and 0.698 inches

Thread Qty Per Inch (tpi):

28

Min. Tensile Strength (psi):

160000 pounds per square inch

Hardness Rating:

36.0 rockwell c and 40.0 rockwell c

Surface Finish:

63.0 microinches bearing surface of head

Material:

Steel comp e4340 fastener or steel comp 4140 fastener or steel comp 8740 fastener or steel comp 8735 fastener or steel comp 6150 fastener

Surface Treatment:

Cadmium fastener and chromate fastener

Surface Treatment Specification:

Qq-p-416 type 2 class 2 federal specification single treatment response fastener

Thread Series Designator:

Unjf

Specification Data:

80205-nas1224 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0