

View Online at <https://aerobasegroup.com/nsn/5306-01-123-9783>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.663 inches and 0.713 inches

**Fastener Length:**

Between 2.048 inches and 2.078 inches

**Head Style:**

Double hexagon w/hole

**Head Height:**

0.405 inches

**Width Between Flats:**

Between 0.492 inches and 0.502 inches

**Extended Washer Diameter:**

Between 0.715 inches and 0.725 inches

**Extended Washer Thickness:**

0.075 inches

**Grip Diameter:**

Between 0.3735 inches and 0.3745 inches

**Thread Diameter:**

0.375 inches

**Grip Length:**

Between 1.365 inches and 1.385 inches

**Thready Qty Per Inch (tpi):**

24

**Min. Tensile Strength (psi):**

220000 pounds per square inch

**Hardness Rating:**

46.0 rockwell c and 50.0 rockwell c

**Material:**

Steel comp h11

**Material Specification:**

Ams 6485 assn standard single material response or ams 6487 assn standard single material response

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

Nas 672 assn standard single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0