NSN 5306-01-123-9790

Close Tolerance Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-123-9790 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.453 inches and 0.489 inches **Fastener Length:** Between 2.031 inches and 2.051 inches **Head Style:** Dished hexagon **Head Height:** Between 0.157 inches and 0.172 inches Width Between Flats: Between 0.492 inches and 0.502 inches **Grip Diameter:** Between 0.3115 inches and 0.3120 inches **Shank Unthreaded Hole Diameter:** 0.076 inches all holes and 0.086 inches all holes **Thread Diameter:** 0.312 inches **Grip Length:** Between 1.562 inches and 1.578 inches Thready Qty Per Inch (tpi): 24 Distance From Head Largest Bearing Surface To Shank Hole Center: 1.946 inches all holes and 1.976 inches all holes **Surface Finish:** 63.0 microinches grip **Special Features:** With retaining element on shank and two holes spaced ninety degrees apart Material: Steel comp xm-13 **Material Specification:** Ams5629 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unjf

Shelf Life: N/a

NSN 5306-01-123-9790

Close Tolerance Bolt - Page 2 of 2



	• •				
In	18	<i>(</i>)+	МА	261	ıre:

--

Demilitarization:

No

Fiig:

A003b0