

View Online at <https://aerobasegroup.com/nsn/5306-01-123-9792>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.515 inches and 0.551 inches

**Fastener Length:**

Between 2.281 inches and 2.301 inches

**Head Style:**

Dished hexagon

**Head Height:**

Between 0.189 inches and 0.204 inches

**Width Between Flats:**

Between 0.553 inches and 0.564 inches

**Grip Diameter:**

Between 0.3740 inches and 0.3745 inches

**Shank Unthreaded Hole Diameter:**

0.106 inches all holes and 0.116 inches all holes

**Thread Diameter:**

0.375 inches

**Grip Length:**

Between 1.750 inches and 1.766 inches

**Thready Qty Per Inch (tpi):**

24

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

2.173 inches all holes and 2.213 inches all holes

**Surface Finish:**

63.0 microinches bearing surface of head

**Special Features:**

With retaining element on shank and two holes spaced ninety degrees apart

**Material:**

Steel comp xm-13

**Material Specification:**

Ams5629 assn standard single material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0