NSN 5306-01-123-9792

Close Tolerance Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-123-9792 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.515 inches and 0.551 inches **Fastener Length:** Between 2.281 inches and 2.301 inches **Head Style:** Dished hexagon **Head Height:** Between 0.189 inches and 0.204 inches Width Between Flats: Between 0.553 inches and 0.564 inches **Grip Diameter:** Between 0.3740 inches and 0.3745 inches **Shank Unthreaded Hole Diameter:** 0.106 inches all holes and 0.116 inches all holes **Thread Diameter:** 0.375 inches **Grip Length:** Between 1.750 inches and 1.766 inches Thready Qty Per Inch (tpi): 24 Distance From Head Largest Bearing Surface To Shank Hole Center: 2.173 inches all holes and 2.213 inches all holes **Surface Finish:** 63.0 microinches bearing surface of head **Special Features:** With retaining element on shank and two holes spaced ninety degrees apart Material: Steel comp xm-13 **Material Specification:** Ams5629 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:**

Unjf Shelf Life:

N/a

NSN 5306-01-123-9792

Close Tolerance Bolt - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A003b0