NSN 5306-01-124-0507

Machine Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-124-0507 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.381 inches and 0.447 inches **Fastener Length:** Between 0.453 inches and 0.499 inches **Head Style:** Hexagon **Head Height:** Between 0.109 inches and 0.141 inches Width Between Flats: Between 0.365 inches and 0.377 inches **Locking Feature:** Patch threads or pellet threads or strip threads **Thread Diameter:** 0.190 inches **Grip Length:** Between 0.052 inches and 0.072 inches **Features Provided:** Finished head Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 125000 pounds per square inch Hardness Rating: 26.0 rockwell c and 32.0 rockwell c Material: Steel comp 431 **Material Specification:** Mil-c-18732 military specification single material response **Surface Treatment: Passivate Thread Series Designator:** Unf Shelf Life: N/a **Unit Of Measure:**

Demilitarization: No

NSN 5306-01-124-0507

Machine Bolt - Page 2 of 2



Fiig:

A003b0

Mil-std (military Standard):

Mil-c-18732 spec.