## NSN 5306-01-124-0511

Shear Bolt - Page 1 of 2

**Thread Class:** 

View Online at https://aerobasegroup.com/nsn/5306-01-124-0511



## 3a **Thread Direction: Right-hand Thread Length:** Between 1.100 inches and 1.150 inches Fastener Length: Between 2.360 inches and 2.390 inches **Head Style:** Double hexagon extended washer **Head Height:** 0.673 inches Width Between Flats: Between 0.803 inches and 0.814 inches **Extended Washer Diameter:** Between 1.185 inches and 1.195 inches **Extended Washer Thickness:** 0.125 inches Grip Diameter: Between 0.6230 inches and 0.6240 inches Single Shear Strength: 132000 pounds per square inch **Thread Diameter:** 0.625 inches Grip Length: Between 1.240 inches and 1.260 inches Thready Qty Per Inch (tpi): 18 Min. Tensile Strength (psi): 220000 pounds per square inch Hardness Rating: 46.0 rockwell c and 50.0 rockwell c Material: Steel comp h11 **Material Specification:** Ams 6485 assn standard single material response or ams 6487 assn standard single material response **Surface Treatment:** Cadmium **Surface Treatment Specification:**

Nas 672 assn standard single treatment response

## **Thread Series Designator:**

Unjf

## NSN 5306-01-124-0511

Shear Bolt - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A003b0

