NSN 5306-01-124-1232

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-124-1232

view Offilite at https://defobasegroup.com/nsn/3300-01-124-1232
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.475 inches and 0.525 inches
Fastener Length:
Between 1.735 inches and 1.765 inches
Head Style:
Double hexagon extended washer
Head Height:
0.254 inches
Width Between Flats:
Between 0.304 inches and 0.313 inches
Extended Washer Diameter:
Between 0.465 inches and 0.475 inches
Extended Washer Thickness:
0.042 inches
Grip Diameter:
Between 0.2485 inches and 0.2495 inches
Single Shear Strength:
132000 pounds per square inch
Thread Diameter:
0.250 inches
Grip Length:
Between 1.240 inches and 1.260 inches
Thready Qty Per Inch (tpi):
28
Min. Tensile Strength (psi):
220000 pounds per square inch
Hardness Rating:
46.0 rockwell c and 50.0 rockwell c
Material:
Steel comp h11
Material Specification:
Ams 6485 assn standard single material response or ams 6487 assn standard single material response
Surface Treatment:
Cadmium
Surface Treatment Specification:
Nas 672 assn standard single treatment response
Thread Series Designator:

Unjf

NSN 5306-01-124-1232

Shear Bolt - Page 2 of 2



_					
c	hο	JIF.		.ife:	
J	116		_	.II C.	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0