## NSN 5306-01-124-1233

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-124-1233

View Online at https://aerobasegroup.com/nsn/5306-01-124-1233			
Thread Class:			
3a			
Thread Direction:			
Right-hand			
Thread Length:			
Between 1.100 inches and 1.150 inches			
Fastener Length:			
Between 3.047 inches and 3.077 inches			
Head Style:			
Double hexagon extended washer			
Head Height:			
0.673 inches			
Width Between Flats:			
Between 0.803 inches and 0.814 inches			
Extended Washer Diameter:			
Between 1.185 inches and 1.195 inches			
Extended Washer Thickness:			
0.125 inches			
Grip Diameter:			
Between 0.6230 inches and 0.6240 inches			
Single Shear Strength:			
132000 pounds per square inch			
Thread Diameter:			
0.625 inches			
Grip Length:			
Between 1.927 inches and 1.947 inches			
Thready Qty Per Inch (tpi):			
18			
Min. Tensile Strength (psi):			
220000 pounds per square inch			
Hardness Rating:			
46.0 rockwell c and 50.0 rockwell c			
Material:			
Steel comp h11			
Material Specification:			
Ams 6485 assn standard single material response or ams 6487 assn standard single material response			
Surface Treatment:			
Cadmium			
Surface Treatment Specification:			
Nas 672 assn standard single treatment response			
Thread Series Designator:			

Unjf

## NSN 5306-01-124-1233

Shear Bolt - Page 2 of 2



She	lf	I if	ρ.
~	•••		•

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A003b0