NSN 5306-01-124-3074

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-124-3074

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.553 inches and 0.603 inches
Fastener Length:
Between 1.063 inches and 1.093 inches
Head Style:
Dished hexagon
Head Height:
Between 0.188 inches and 0.203 inches
Width Between Flats:
Between 0.553 inches and 0.564 inches
Grip Diameter:
Between 0.3735 inches and 0.3745 inches
Thread Diameter:
0.375 inches
Grip Length:
Between 0.490 inches and 0.510 inches
Thready Qty Per Inch (tpi):
24
Min. Tensile Strength (psi):
160000 pounds per square inch
Hardness Rating:
36.0 rockwell c and 40.0 rockwell c
Surface Finish:
32.0 microinches threads
Material:
Steel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 8735 or steel comp 6150
Surface Treatment:
Cadmium
Surface Treatment Specification:
Qq-p-416 ty1 federal specification single treatment response
Thread Series Designator:
Unjf
Specification Data:
80205-nas1306 professional/industrial association standard
Shelf Life:
N/a
Unit Of Measure:

NSN 5306-01-124-3074

Shear Bolt - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0