NSN 5306-01-124-3075

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-124-3075

View Online at https://aerobasegroup.com/nsn/5306-01-124-3075
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.553 inches and 1.603 inches
Fastener Length:
Between 1.125 inches and 1.155 inches
Head Style:
Dished hexagon
Head Height:
Between 0.188 inches and 0.203 inches
Width Between Flats:
Between 0.553 inches and 0.564 inches
Grip Diameter:
Between 0.3735 inches and 0.3745 inches
Thread Diameter:
0.375 inches
Grip Length:
Between 0.552 inches and 0.572 inches
Thready Qty Per Inch (tpi):
24
Min. Tensile Strength (psi):
Min. Tensile Strength (psi): 160000 pounds per square inch
160000 pounds per square inch
160000 pounds per square inch Hardness Rating:
160000 pounds per square inch Hardness Rating: 36.0 rockwell c and 40.0 rockwell c
160000 pounds per square inch Hardness Rating: 36.0 rockwell c and 40.0 rockwell c Surface Finish:
160000 pounds per square inch Hardness Rating: 36.0 rockwell c and 40.0 rockwell c Surface Finish: 63.0 microinches bearing surface of head
160000 pounds per square inch Hardness Rating: 36.0 rockwell c and 40.0 rockwell c Surface Finish: 63.0 microinches bearing surface of head Material:
160000 pounds per square inch Hardness Rating: 36.0 rockwell c and 40.0 rockwell c Surface Finish: 63.0 microinches bearing surface of head Material: Steel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 8735 or steel comp 6150
160000 pounds per square inch Hardness Rating: 36.0 rockwell c and 40.0 rockwell c Surface Finish: 63.0 microinches bearing surface of head Material: Steel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 8735 or steel comp 6150 Surface Treatment:
160000 pounds per square inch Hardness Rating: 36.0 rockwell c and 40.0 rockwell c Surface Finish: 63.0 microinches bearing surface of head Material: Steel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 8735 or steel comp 6150 Surface Treatment: Cadmium
160000 pounds per square inch Hardness Rating: 36.0 rockwell c and 40.0 rockwell c Surface Finish: 63.0 microinches bearing surface of head Material: Steel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 8735 or steel comp 6150 Surface Treatment: Cadmium Surface Treatment Specification:
160000 pounds per square inch Hardness Rating: 36.0 rockwell c and 40.0 rockwell c Surface Finish: 63.0 microinches bearing surface of head Material: Steel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 8735 or steel comp 6150 Surface Treatment: Cadmium Surface Treatment Specification: Qq-p-416 ty1 federal specification single treatment response
160000 pounds per square inch Hardness Rating: 36.0 rockwell c and 40.0 rockwell c Surface Finish: 63.0 microinches bearing surface of head Material: Steel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 8735 or steel comp 6150 Surface Treatment: Cadmium Surface Treatment Specification: Qq-p-416 ty1 federal specification single treatment response Thread Series Designator:
160000 pounds per square inch Hardness Rating: 36.0 rockwell c and 40.0 rockwell c Surface Finish: 63.0 microinches bearing surface of head Material: Steel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 8735 or steel comp 6150 Surface Treatment: Cadmium Surface Treatment Specification: Qq-p-416 ty1 federal specification single treatment response Thread Series Designator: Unjf
160000 pounds per square inch Hardness Rating: 36.0 rockwell c and 40.0 rockwell c Surface Finish: 63.0 microinches bearing surface of head Material: Steel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 8735 or steel comp 6150 Surface Treatment: Cadmium Surface Treatment Specification: Qq-p-416 ty1 federal specification single treatment response Thread Series Designator: Unjf Specification Data:
160000 pounds per square inch Hardness Rating: 36.0 rockwell c and 40.0 rockwell c Surface Finish: 63.0 microinches bearing surface of head Material: Steel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 8735 or steel comp 6150 Surface Treatment: Cadmium Surface Treatment Specification: Qq-p-416 ty1 federal specification single treatment response Thread Series Designator: Unjf Specification Data: 80205-nas1306 professional/industrial association standard
160000 pounds per square inch Hardness Rating: 36.0 rockwell c and 40.0 rockwell c Surface Finish: 63.0 microinches bearing surface of head Material: Steel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 8735 or steel comp 6150 Surface Treatment: Cadmium Surface Treatment Specification: Qq-p-416 ty1 federal specification single treatment response Thread Series Designator: Unjf Specification Data: 80205-nas1306 professional/industrial association standard Shelf Life:

--

NSN 5306-01-124-3075

Shear Bolt - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0