

View Online at <https://aerobasegroup.com/nsn/5306-01-124-5243>

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

2.000 inches

Fastener Length:

11.188 inches

Head Style:

Flat chamfer

Head Diameter:

2.250 inches

Head Height:

1.500 inches

Locking Feature:

Pellet threads

First Diameter From Head:

1.500 inches

Second Diameter From Head:

1.345 inches

Third Diameter From Head:

1.500 inches

Distance From Largest Bearing Surface Of Head To End Of First Diameter:

2.938 inches

Distance From Largest Bearing Surface Of Head To End Of Second Diameter:

8.313 inches

Distance From Largest Bearing Surface Of Head To End Of Third Diameter:

8.563 inches

Internal Drive Style:

Hexagon

Thread Diameter:

1.500 inches

Width Across Flats:

1.000 inches

Thready Qty Per Inch (tpi):

8

Min. Tensile Strength (psi):

135000 pounds per square inch

Hardness Rating:

279.0 brinell standard and 300.0 brinell standard

Minimum Yield Strength:

115000 pounds per square inch

Externally Relieved Body Diameter Quantity:

3

Surface Finish:

63.0 microinches grip

Material:

Steel comp 4140

Material Specification:

Mil-s5626 military specification single material response

Thread Series Designator:

Un

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0

Mil-std (military Standard):

spec.