Externally Relieved Body Bolt - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5306-01-124-5776

| Thread C   | lass:   |
|------------|---|
| 3a         |   |
| Thread D   | irection:   |
| Right-har  | d   |
| Thread L   | ength:  |
| 0.405 inc  | hes   |
| Fastener   | Length:   |
| 0.840 inc  | hes   |
| Head Sty   | le:   |
| Hexagon    |   |
| Head He    | ght:  |
| 0.156 inc  | hes   |
| Width Be   | tween Flats:  |
| Between    | 0.430 inches and 0.439 inches                                   |
| First Dia  | neter From Head:  |
| Between    | 0.246 inches and 0.249 inches                                   |
| Second I   | Diameter From Head:   |
| Between    | 0.190 inches and 0.195 inches                                   |
| Distance   | From Largest Bearing Surface Of Head To End Of Second Diameter: |
| Between    | 0.395 inches and 0.435 inches                                   |
| Thread D   | iameter:  |
| 0.250 inc  | hes   |
| Thready    | Qty Per Inch (tpi):   |
| 28         |   |
| External   | y Relieved Body Diameter Quantity:                              |
| 2          |   |
| Material:  |   |
| Stainless  | steel   |
| Material   | Specification:  |
| 5708 ass   | n standard single material response                             |
| Thread S   | eries Designator:   |
| Unjf       |   |
| Shelf Life | e:  |
| N/a        |   |
| Unit Of N  | leasure:  |
|            |   |
| Demilitar  | ization:  |
| No         |   |
| Fiig:      |   |
| -          |   |