Externally Relieved Body Bolt - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5306-01-124-6451

| Thread Class:    |   |
|------------------|---|
| 3a               |   |
| Thread Direction | on:   |
| Right-hand       |   |
| Thread Length    | :   |
| 0.780 inches     |   |
| Fastener Leng    | th:   |
|                  | inches and 1.020 inches                                   |
| Head Style:      |   |
| Hexagon          |   |
| Head Height:     |   |
| 0.500 inches     |   |
| Width Betweer    | ) Flats:  |
| 1.375 inches     |   |
| First Diameter   | From Head:  |
| Between 1.067    | inches and 1.072 inches                                   |
| Distance From    | Largest Bearing Surface Of Head To End Of First Diameter: |
| Between 0.125    | inches and 0.140 inches                                   |
| Thread Diamet    | er:   |
| 1.188 inches     |   |
| Thready Qty Po   | er Inch (tpi):  |
| 12               |   |
| Hardness Ratii   | ng:   |
| 23.0 rockwell c  | and 32.0 rockwell c                                       |
| Externally Reli  | eved Body Diameter Quantity:                              |
| 1                |   |
| Material:        |   |
| Steel            |   |
| Surface Treatn   | nent:   |
| Cadmium          |   |
| Thread Series    | Designator:   |
| Un               |   |
| Shelf Life:      |   |
| N/a              |   |
| Unit Of Measur   | e:  |
|                  |   |
| Demilitarizatio  | n:  |
| No               |   |
| Fiig:            |   |
| A003b0           |   |