NSN 5306-01-125-9020

Shear Bolt - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5306-01-125-9020



Thread Class: 3a **Thread Direction: Right-hand Thread Length:** Between 0.444 inches and 0.494 inches Fastener Length: Between 1.516 inches and 1.546 inches **Head Style:** Dished hexagon **Head Height:** Between 0.156 inches and 0.171 inches Width Between Flats: Between 0.492 inches and 0.502 inches Hole Diameter: Between 0.070 inches and 0.080 inches **Grip Diameter:** Between 0.3110 inches and 0.3120 inches **Thread Diameter:** 0.312 inches Grip Length: Between 1.052 inches and 1.072 inches **Hole Quantity:** Hole Type: Drilled Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 36.0 rockwell c and 40.0 rockwell c Hole Configuration Style: Hexagon corners Surface Finish: 63.0 microinches grip Material: Steel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 8735 or steel comp 6150 Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416 type 2 class 2 federal specification single treatment response

3

NSN 5306-01-125-9020

Shear Bolt - Page 2 of 2



Thread Series Designator:

Unjf

Specification Data:

80205-nas1305 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0