

View Online at <https://aerobasegroup.com/nsn/5306-01-126-1201>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 1.621 inches and 1.671 inches

**Fastener Length:**

Between 4.506 inches and 4.536 inches

**Head Style:**

Hexagon

**Head Height:**

Between 0.625 inches and 0.640 inches

**Width Between Flats:**

Between 1.801 inches and 1.815 inches

**Grip Diameter:**

Between 1.2475 inches and 1.2490 inches

**Shank Unthreaded Hole Diameter:**

0.141 inches first hole and 0.151 inches first hole

**Thread Diameter:**

1.250 inches

**Grip Length:**

Between 2.865 inches and 2.885 inches

**Thread Qty Per Inch (tpi):**

12

**Min. Tensile Strength (psi):**

180000 pounds per square inch

**Hardness Rating:**

39.0 rockwell c and 43.0 rockwell c

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

4.107 inches first hole and 4.157 inches first hole

**Surface Finish:**

32.0 microinches threads

**Material:**

Steel comp e4340 or steel comp 8740

**Material Specification:**

Mil-s-5000 military specification 1st material response or mil-s-6049 military specification 2nd material response or ams 6322 assn standard 2nd material response

**Surface Treatment:**

Cadmium and chromate

**Surface Treatment Specification:**

Qq-p-416 type 2 class 2 federal specification single treatment response

**Thread Series Designator:**

Unjf

**Specification Data:**

80205-nas1970 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0

**Mil-std (military Standard):**

Mil-s-5000 spec.