

View Online at <https://aerobasegroup.com/nsn/5306-01-126-1201>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 1.621 inches and 1.671 inches

Fastener Length:

Between 4.506 inches and 4.536 inches

Head Style:

Hexagon

Head Height:

Between 0.625 inches and 0.640 inches

Width Between Flats:

Between 1.801 inches and 1.815 inches

Grip Diameter:

Between 1.2475 inches and 1.2490 inches

Shank Unthreaded Hole Diameter:

0.141 inches first hole and 0.151 inches first hole

Thread Diameter:

1.250 inches

Grip Length:

Between 2.865 inches and 2.885 inches

Thread Qty Per Inch (tpi):

12

Min. Tensile Strength (psi):

180000 pounds per square inch

Hardness Rating:

39.0 rockwell c and 43.0 rockwell c

Distance From Head Largest Bearing Surface To Shank Hole Center:

4.107 inches first hole and 4.157 inches first hole

Surface Finish:

32.0 microinches threads

Material:

Steel comp e4340 or steel comp 8740

Material Specification:

Mil-s-5000 military specification 1st material response or mil-s-6049 military specification 2nd material response or ams 6322 assn standard 2nd material response

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416 type 2 class 2 federal specification single treatment response

Thread Series Designator:

Unjf

Specification Data:

80205-nas1970 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5000 spec.