## NSN 5306-01-126-1621

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-126-1621 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.589 inches and 0.639 inches **Fastener Length:** Between 1.474 inches and 1.504 inches **Head Style:** Spline extended washer **Head Height:** Between 0.263 inches and 0.303 inches **Extended Washer Diameter:** Between 0.691 inches and 0.701 inches **Extended Washer Thickness:** Between 0.044 inches and 0.064 inches **Grip Diameter:** Between 0.3740 inches and 0.3745 inches **Head Minor Diameter:** Between 0.448 inches and 0.455 inches **Thread Diameter:** 0.375 inches **Grip Length:** Between 0.865 inches and 0.885 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 180000 pounds per square inch **Product Name:** Navy special project Material: Steel comp xm-13 **Material Specification:** Ams 5629 assn standard single material response **Surface Treatment:** 

Passivate

**Surface Treatment Specification:** 

Qq-p-35 federal specification single treatment response

**Thread Series Designator:** 

Unjf

Shelf Life:

N/a

## NSN 5306-01-126-1621

Shear Bolt - Page 2 of 2



	• •				
In	18	<i>(</i> )+	МЛО	201	ure:

--

Demilitarization:

No

Fiig:

A003b0