NSN 5306-01-126-2321

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-126-2321

| View Online at https://aerobasegroup.com/nsn/5306-01-126-2321 |
|--|
| Thread Class: |
| 3a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| Between 0.345 inches and 0.395 inches |
| Fastener Length: |
| Between 1.480 inches and 1.510 inches |
| Head Style: |
| Dished hexagon |
| Head Height: |
| Between 0.125 inches and 0.140 inches |
| Width Between Flats: |
| Between 0.429 inches and 0.439 inches |
| Grip Diameter: |
| Between 0.2490 inches and 0.2495 inches |
| Thread Diameter: |
| 0.250 inches |
| Grip Length: |
| Between 1.115 inches and 1.135 inches |
| Thready Qty Per Inch (tpi): |
| 28 |
| Min. Tensile Strength (psi): |
| 160000 pounds per square inch |
| Surface Finish: |
| 32.0 microinches threads |
| Material: |
| Iron alloy 660 |
| Material Specification: |
| Ams5731 assn standard single material response or ams5737 assn standard single material response |
| Surface Treatment: |
| Cadmium and chromate |
| Surface Treatment Specification: |
| Qq-p-416, type 2, cl2 federal specification single treatment response |
| Thread Series Designator: |
| Tillead Selles Designator. |
| Unjf |
| |
| Unjf |
| Unjf Specification Data: |
| Unjf Specification Data: 80205-nas6304 professional/industrial association standard |
| Unjf Specification Data: 80205-nas6304 professional/industrial association standard Shelf Life: |

--

NSN 5306-01-126-2321

Shear Bolt - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0