

View Online at <https://aerobasegroup.com/nsn/5306-01-126-8792>

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

2.750 inches

Fastener Length:

12.000 inches

Head Style:

Hexagon

Head Height:

1.344 inches

Width Between Flats:

3.000 inches

Shank Unthreaded Hole Diameter:

0.203 inches first hole and 0.213 inches first hole

Thread Diameter:

2.000 inches

Features Provided:

Finished head

Thready Qty Per Inch (tpi):

4-1/2

Min. Tensile Strength (psi):

60000 pounds per square inch

Hardness Rating:

70.0 rockwell c and 100.0 rockwell c

Minimum Yield Strength:

36000 pounds per square inch

Distance From Head Largest Bearing Surface To Shank Hole Center:

11.500 inches first hole

Material:

Steel comp 1013 or steel comp 1015 or steel comp 1016 or steel comp 1017 or steel comp 1018 or steel comp 1019 or steel comp 1020 or steel comp 1021 or steel comp 1022 or steel comp 1023 or steel comp 1025 or steel comp 1026 or steel comp 1029 or steel comp 1030 or steel comp 1033 or steel comp 1034 or steel comp 1035 or steel comp 1037 or steel comp 1038 or steel comp 1039 or steel comp 1040 or steel comp 1524 or steel comp 1527 or steel comp 1536 or steel comp 1541 or steel comp 1005 or steel comp 1006 or steel comp 1008 or steel comp 1009 or steel comp 1010 or steel comp 1011

Material Specification:

Sae j429 assn standard single material response

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Fig:

A003b0