Externally Relieved Body Bolt - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5306-01-128-4454

| view Online at https://aerobasegroup.com/hsn/5506-01-126-4454 |
|---|
| Thread Class: |
| 3a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| 0.779 inches |
| Fastener Length: |
| 1.062 inches |
| Head Style: |
| Double hexagon w/hole |
| Head Height: |
| 0.260 inches |
| Width Between Flats: |
| Between 0.243 inches and 0.251 inches |
| Extended Washer Diameter: |
| 0.375 inches |
| Extended Washer Thickness: |
| Between 0.060 inches and 0.070 inches |
| First Diameter From Head: |
| 0.227 inches |
| Distance From Largest Bearing Surface Of Head To End Of First Diameter: |
| 0.312 inches |
| Thread Diameter: |
| 0.250 inches |
| Thready Qty Per Inch (tpi): |
| 28 |
| Externally Relieved Body Diameter Quantity: |
| 1 |
| Material: |
| Iron alloy 660 |
| Material Specification: |
| Ams 5731 assn standard single material response |
| Thread Series Designator: |
| Unjf |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A003b0 |